

IN THE CLAIMS:

Amend the claims as indicated below.

1 1. (currently amended) A method for a spread spectrum detector, comprising the steps
2 of:
3 receiving a spread spectrum modulated signal having a Doppler shift error imposed by
4 movement between a signal source and a receiver;
5 producing a plurality of complex first correlation values based upon the signal and a
6 code;
7 generating a plurality of complex second correlation values respectively from the first
8 correlation values, wherein generating includes combining a stored, associated, phase shift value
9 with each of the first correlation values to produce the second correlation values~~the second~~
10 ~~correlation values being phase shifted by respective different amounts from corresponding first~~
11 ~~correlation values, so that the second correlation values exhibit less of the Doppler shift error~~
12 ~~than the first correlation values; and~~
13 combining the second correlation values to derive a complex third correlation value that
14 indicates a degree of correspondence of the code with the signal.

As Cont
1 2. (original) The method of claim 1, further comprising the steps of:
2 performing the producing, generating, and integrating steps a plurality of times with a
3 different code phase of the code each time in order to produce a plurality of third correlation
4 values; and
5 determining that a particular one of the code phases corresponds to the signal based upon
6 the third correlation values.

1 3. (original) The method of claim 1, wherein the producing step comprises the steps of:
2 multiplying chips of the code with signal samples, respectively, to derive multiplication
3 results; and
4 adding together the multiplication results to produce the first correlation values.

1 4. (original) The method of claim 1, wherein the step of generating the second
2 correlation values comprises the step of combining successive first correlation values with an

3 incrementally different phase so that each of the second correlation values is offset by a different
4 phase shift.

1 5. (original) The method of claim 1, wherein the second correlation values are
2 combined coherently in the combining step so that the third correlation value comprises a real
3 number part and an imaginary number part, which are collectively indicative of a magnitude and
4 a phase.

1 6. (original) The method of claim 1, wherein the second correlation values are
2 combined noncoherently in the combining step so that the third correlation value comprises a
3 magnitude.

1 7. (original) The method of claim 1, wherein the producing step comprises the step of
2 using a matched filter to produce the first correlation values.

As
Cont
1 8. (original) The method of claim 1, wherein the producing step comprises the step of
2 using a digital signal processor to produce the first correlation values.

1 9. (original) The method of claim 1, wherein the signal is received from a satellite
2 associated with a global positioning system.

1 10. (original) The method of claim 1, wherein the signal is a carrier signal modulated
2 with a repeating code.

1 11. (original) The method of claim 2, wherein the determining step is performed by a
2 processor.

1 12. (original) The method of claim 1, wherein the generating step comprises the step of
2 combining a phase shift value with each of the first correlation values to produce the second
3 correlation values.

1 13. (currently amended) ~~The method of claim 12, further~~ A method for a spread
2 spectrum detector, comprising the steps of:
3 receiving a spread spectrum modulated signal having a Doppler shift error imposed by

4 movement between a signal source and a receiver;

5 producing a plurality of complex first correlation values based upon the signal and a
6 code;

7 generating a plurality of complex second correlation values respectively from the first
8 correlation values, the second correlation values being phase shifted by respective different
9 amounts from corresponding first correlation values, so that the second correlation values exhibit
10 less of the Doppler shift error than the first correlation values, wherein generating includes
11 combining a phase shift value with each of the first correlation values to produce the second
12 correlation values; and

13 combining the second correlation values to derive a complex third correlation value that
14 indicates a degree of correspondence of the code with the signal;

15 providing a look-up table storing a plurality of phase shift values;

16 providing a counter that produces indices for the look-up table;

17 identifying the phase shift value for each of the first correlation values based upon the
18 indices and the look-up table; and

19 multiplying each first correlation value with each phase shift value to produce each
20 second correlation value.

1 14. (currently amended) A spread spectrum detector, comprising:

2 first means for receiving a spread spectrum modulated signal having a Doppler shift error
3 imposed by movement between a signal source and a receiver;

4 second means for producing a plurality of complex first correlation values based upon the
5 signal and a code;

6 third means for generating a plurality of complex second correlation values respectively
7 from the first correlation values, wherein generating includes combining a stored, associated,
8 phase shift value with each of the first correlation values to produce the second correlation
9 values~~the second correlation values being phase shifted by respective different amounts from~~
10 ~~corresponding first correlation values, so that the second correlation values exhibit less of the~~
11 ~~Doppler shift error than the first correlation values; and~~

12 fourth means for combining the second correlation values to derive a third correlation

13 value that indicates a degree of correspondence of the code with the signal.

1 15. (original) The detector of claim 14, further comprising:
2 fifth means for determining that a code phase of the code corresponds to the signal based
3 upon the third correlation value.

1 16. (original) The detector of claim 14, wherein the second means comprise:
2 means for multiplying chips of the code with signal samples, respectively, to derive
3 multiplication results; and
4 means for adding together the multiplication results to produce the first correlation
5 values.

1 17. (original) The detector of claim 14, wherein the third means comprises a means for
2 combining successive first correlation values with an incrementally different phase so that each
3 of the second correlation values is offset by a different phase shift.

1 18. (original) The detector of claim 14, wherein the fourth means comprises a means for
2 coherently combining the second correlation values together so that the third correlation value
3 comprises a real number part and an imaginary number part, which are collectively indicative of
4 a magnitude and a phase.

1 19. (original) The detector of claim 14, wherein the fourth means comprises a means for
2 noncoherently combining the second correlation values together so that the third correlation
3 value comprises a magnitude and no phase information.

1 20. (original) The detector of claim 14, wherein the second means comprises a matched
2 filter means for producing the first correlation values.

1 21. (original) The detector of claim 14, wherein the second means comprises a digital
2 signal processor to produce the first correlation values.

1 22. (original) The detector of claim 14, wherein the signal is received from a satellite
2 associated with a global positioning system.

1 23. (original) The detector of claim 14, wherein the signal is a carrier signal modulated
2 with a repeating code.

1 24. (original) The detector of claim 14, wherein the third means comprises means for
2 combining a phase shift value with each of the first correlation values to produce the second
3 correlation values.

1 25. (currently amended) ~~The detector of claim 24, wherein the third means further~~
2 ~~comprises~~ A spread spectrum detector, comprising:
3 first means for receiving a spread spectrum modulated signal having a Doppler shift error
4 imposed by movement between a signal source and a receiver;
5 second means for producing a plurality of complex first correlation values based upon the
6 signal and a code;

7 third means for generating a plurality of complex second correlation values respectively
8 from the first correlation values, the second correlation values being phase shifted by respective
9 different amounts from corresponding first correlation values, so that the second correlation
10 values exhibit less of the Doppler shift error than the first correlation values wherein the third
11 means comprises, wherein the third means comprises,

12 means for storing a plurality of phase shift values;
13 means for identifying the phase shift value for each of the first correlation values; and
14 means for multiplying each first correlation value with each phase shift value to
15 produce each second correlation value; and

16 means for combining a phase shift value with each of the first correlation values to
17 produce the second correlation values; and

18 fourth means for combining the second correlation values to derive a complex third
19 correlation value that indicates a degree of correspondence of the code with the signal.

1 26. (currently amended) A spread spectrum detector, comprising:
2 a receiver configured to receive a spread spectrum modulated signal having a Doppler
3 shift error imposed by movement between a signal source and a receiver;

4 a multiplier configured to produce a plurality of complex first correlation values based
5 upon the signal and a code;

6 a phase shifter configured to generate a plurality of complex second correlation values
7 respectively from the first correlation values, wherein generating includes combining a stored,
8 associated, phase shift value with each of the first correlation values to produce the second
9 correlation values~~the second correlation values being phase shifted by respective different~~
10 ~~amounts from corresponding first correlation values, so that the second correlation values exhibit~~
11 ~~less of the Doppler shift error than the first correlation values; and~~

12 an integrator configured to integrate the second correlation values to derive a third
13 correlation value that indicates a degree of correspondence of the code with the signal.

1 27. (original) The spread spectrum detector of claim 26, further comprising:
2 a processor programmed to determine that a particular one of code phases of the code
3 corresponds to the signal based upon the third correlation value.

1 28. (original) The detector of claim 26, wherein the multiplier comprises:
2 a plurality of multipliers configured to multiply chips of each code phase with signal
3 samples, respectively, to derive the multiplication results; and
4 adders configured to add together the multiplication results to produce the first correlation
5 values.

1 29. (original) The detector of claim 26, wherein the phase shifter is configured to
2 successively combine first correlation values with an incrementally different phase so that each
3 of the second correlation values is offset by a different phase shift.

1 30. (original) The detector of claim 26, wherein the integrator is configured to coherently
2 combine the second correlation values together so that the third correlation value comprises a
3 real number part and an imaginary number part, which are collectively indicative of a magnitude
4 and a phase.

1 31. (original) The detector of claim 26, wherein the integrator is configured to
2 noncoherently combine the second correlation values together so that the third correlation value

3 comprises a magnitude and no phase information.

1 32. (original) The detector of claim 26, wherein the multiplier comprises a matched filter
2 configured to produce the first correlation values.

1 33. (original) The detector of claim 26, wherein the multiplier comprises a digital signal
2 processor to produce the first correlation values.

1 34. (original) The detector of claim 26 wherein the signal is received from a satellite
2 associated with a global positioning system.

1 35. (original) The detector of claim 26, wherein the signal is a carrier signal modulated
2 with a repeating code.

1 36. (original) The detector of claim 26, wherein the phase shifter comprises a mixer for
2 combining a phase shift value with each of the first correlation values to produce the second
3 correlation values.

1 37. (currently amended) ~~The detector of claim 36, wherein the phase shifter further~~
2 ~~comprises~~ A spread spectrum detector, comprising:

3 a receiver configured to receive a spread spectrum modulated signal having a Doppler
4 shift error imposed by movement between a signal source and a receiver;

5 a multiplier configured to produce a plurality of complex first correlation values based
6 upon the signal and a code;

7 a phase shifter configured to generate a plurality of complex second correlation values
8 respectively from the first correlation values, the second correlation values being phase shifted by
9 respective different amounts from corresponding first correlation values, so that the second
10 correlation values exhibit less of the Doppler shift error than the first correlation values, wherein
11 the phase shifter comprises a mixer for combining a phase shift value with each of the first
12 correlation values to produce the second correlation values;

13 an integrator configured to integrate the second correlation values to derive a third
14 correlation value that indicates a degree of correspondence of the code with the signal;

15 a memory for storing a plurality of phase shift values; and
16 a counter producing addresses in the memory to identify phase shift values for the first
17 correlation values, respectively.

1 38. (currently amended) A computer readable medium having a program for operating a
2 spread spectrum detector, the program comprising:
3 first logic configured to receive a spread spectrum modulated signal having a Doppler
4 shift error imposed by movement between a signal source and a receiver;
5 second logic configured to produce a plurality of complex first correlation values based
6 upon the signal and a code;
7 third logic configured to generate a plurality of complex second correlation values
8 respectively from the first correlation values, wherein generating includes combining a stored
9 associated, phase shift value with each of the first correlation values to produce the second
10 correlation values~~the second correlation values being phase shifted by respective different~~
11 ~~amounts from corresponding first correlation values, so that the second correlation values exhibit~~
12 ~~less of the Doppler shift error than the first correlation values; and~~
13 fourth logic configured to combine the second correlation values to derive a complex
14 third correlation value that indicates a degree of correspondence of the code with the signal.

A2
cont

1 39. (original) The computer readable medium as defined in claim 38, further comprising:
2 fifth logic configured to cause the second, third and fourth logics to perform the
3 producing, generating, and combining steps a plurality of times with a different code phase of the
4 code each time in order to produce a plurality of third correlation values; and
5 sixth logic configured to determine that a particular one of the code phases corresponds to
6 the signal based upon the third correlation values.

1 40. (original) The computer readable medium as defined in claim 38, wherein the second
2 logic comprises:
3 logic configured to multiply chips of the code with signal samples, respectively, to derive
4 the multiplication results; and
5 logic configured to add together the multiplication results to produce the first correlation

6 values.

1 41. (original) The computer readable medium as defined in claim 38, wherein the third
2 logic comprises logic configured to combine successive first correlation values with an
3 incrementally different phase so that each of the second correlation values is offset by a different
4 phase shift.

1 42. (original) The computer readable medium as defined in claim 38, wherein the fourth
2 logic comprises logic to coherently combine the second correlation values to produce the third
3 correlation value so that the third correlation value comprises a real number part and an
4 imaginary number part, which are collectively indicative of a magnitude and a phase.

1 43. (original) The computer readable medium as defined in claim 38, wherein the fourth
2 logic comprises logic to noncoherently combine the second correlation values to produce the
3 third correlation value so that the third correlation value comprises a magnitude without phase
4 information.

1 44. (original) The computer readable medium as defined in claim 38, wherein the second
2 logic comprises logic configured to use a matched filter to produce the first correlation values.

1 45. (original) The computer readable medium as defined in claim 38, wherein the second
2 logic comprises logic configured to use a digital signal processor to produce the first correlation
3 values.

1 46. (original) The computer readable medium as defined in claim 38, wherein the first
2 logic is configured to receive a signal from a satellite associated with a global positioning system.

1 47. (original) The computer readable medium as defined in claim 38, wherein the first
2 logic is configured to receive a carrier signal modulated with a repeating code.

1 48. (original) The computer readable medium as defined in claim 38, wherein the third
2 logic comprises logic configured to combine a phase shift value with each of the first correlation
3 values to produce the second correlation values.

1 49. (currently amended) ~~The computer readable medium as defined in claim 48, wherein~~
2 ~~the third logic comprises~~ A computer readable medium having a program for operating a spread
3 spectrum detector, the program comprising:

4 first logic configured to receive a spread spectrum modulated signal having a Doppler
5 shift error imposed by movement between a signal source and a receiver;

6 second logic configured to produce a plurality of complex first correlation values based
7 upon the signal and a code;

8 third logic configured to generate a plurality of complex second correlation values
9 respectively from the first correlation values, the second correlation values being phase shifted by
10 respective different amounts from corresponding first correlation values, so that the second
11 correlation values exhibit less of the Doppler shift error than the first correlation values wherein
12 the third logic comprises,

13 ___ a look-up table storing a plurality of phase shift values;

14 ___ a counter that produces indices for the look-up table; and

15 ___ a multiplier to multiply each first correlation value with a phase shift value to produce
16 a second correlation value; and

17 fourth logic configured to combine the second correlation values to derive a complex
18 third correlation value that indicates a degree of correspondence of the code with the signal.

1 50. (currently amended) A GPS receiver, comprising:

2 a first GPS antenna coupled to a digital memory, the digital memory storing first digitized
3 signals obtained through the first GPS antenna;

4 a second GPS antenna coupled to the digital memory, the digital memory storing second
5 digitized signals obtained through the second GPS antenna;

6 a digital processor coupled to the digital memory, the digital processor processing the first
7 digitized signals after being stored in the digital memory to provide the first position information
8 and processing the second digitized signals after being stored in the digital memory to provide
9 second position information;

10 a receiver configured to receive a spread spectrum modulated signal having a Doppler
11 shift error imposed by movement between a signal source and a receiver;

12 a multiplier configured to produce a plurality of complex first correlation values based
13 upon the signal and a code;

14 a phase shifter configured to generate a plurality of complex second correlation values
15 respectively from the first correlation values, wherein generating includes combining a stored,
16 associated, phase shift value with each of the first correlation values to produce the second
17 correlation values~~the second correlation values being phase shifted by respective different~~
18 ~~amounts from corresponding first correlation values, so that the second correlation values exhibit~~
19 ~~less of the Doppler shift error than the first correlation values; and~~

20 an integrator configured to integrate the second correlation values to derive a third
21 correlation value that indicates~~indicate~~ a degree of correspondence of the code with the signal.

A2
Cont

1 51. (currently amended) A method of operating a GPS receiver, the method comprising:
2 receiving first GPS signals through a first GPS antenna;
3 digitizing the first GPS signals to provide first digitized signals and storing the first
4 digitized signals in a first digital memory;
5 receiving second GPS signals through a second GPS antenna;
6 digitizing the second GPS signals to provide second digitized signals and storing the
7 second digitized signals in one of the first digital memory and a second digital memory;
8 processing in a digital processor the stored first digitized signals to provide a first position
9 information and processing the stored second digitized signals to provide a second position
10 information;
11 selecting one of the first position information and the second position information to
12 provide a selected position information; and
13 when performing the processing step, performing the following steps upon each of the
14 first and second GPS signals;
15 producing a plurality of complex first correlation values based upon the signal and a
16 code;
17 generating a plurality of complex second correlation values respectively from the first
18 correlation values, wherein generating includes combining a stored, associated, phase
19 shift value with each of the first correlation values to produce the second correlation

20 ~~values the second correlation values being phase shifted by respective different amounts~~
21 ~~from corresponding first correlation values, so that the second correlation values exhibit~~
22 ~~less of the Doppler shift error than the first correlation values; and~~
23 combining the second correlation values to derive a complex third correlation value
24 that indicates a degree of correspondence of the code with the signal.

1 52. (currently amended) A method for determining a position of a mobile global
2 positioning system receiver, the mobile global positioning receiver receiving global positioning
3 system signals from at least one of a plurality of global positioning system (GPS) satellites, the
4 method comprising:
5 receiving a cellular communication signal in a mobile communication receiver coupled to
6 the mobile global positioning system receiver, the cellular communication signal having a time
7 indicator which represents a time event;
8 associating the time indicator with data representing a time of arrival of a GPS satellite
9 signal at the mobile global positioning system receiver;
10 determining position information of the mobile global positioning system receiver,
11 wherein the data representing the time of arrival of the GPS satellite signal and the time indicator
12 are used to determine the position information of the mobile global positioning system receiver
13 and wherein the cellular communication signal supports 2-way communications; and
14 when performing the determining step, performing the following steps:
15 producing a plurality of complex first correlation values based upon a signal and a
16 code;
17 generating a plurality of complex second correlation values respectively from the first
18 correlation values, wherein generating includes combining a stored, associated, phase
19 shift value with each of the first correlation values to produce the second correlation
20 values the second correlation values being phase shifted by respective different amounts
21 from corresponding first correlation values, so that the second correlation values exhibit
22 less of the Doppler shift error than the first correlation values; and
23 combining the second correlation values to derive a complex third correlation value
24 that indicates a degree of correspondence of the code with the signal.

1 53. (currently amended) A method of operating a global positioning system (GPS)
2 receiver, comprising:
3 sensing whether GPS signals are capable of being received from GPS satellites and
4 providing an activation signal when GPS signals are capable of being received;
5 maintaining the GPS receiver in a low power state;
6 activating the GPS receiver from the low power state upon detecting the activation signal;
7 producing a plurality of complex first correlation values based upon a GPS signal and a
8 code;
9 generating a plurality of complex second correlation values respectively from the first
10 correlation values, wherein generating includes combining a stored, associated, phase shift value
11 with each of the first correlation values to produce the second correlation values~~the second~~
12 ~~correlation values being phase shifted by respective different amounts from corresponding first~~
13 ~~correlation values, so that the second correlation values exhibit less of the Doppler shift error~~
14 ~~than the first correlation values; and~~
15 combining the second correlation values to derive a complex third correlation value that
16 indicates a degree of correspondence of the code with the signal.

A2
Cont

1 54. (currently amended) A method for using a dual mode GPS receiver, the method
2 comprising the steps of:
3 activating the GPS receiver in a first mode of operation including,
4 receiving GPS signals from in view satellites;
5 downconverting and demodulating the GPS signals to extract Doppler information
6 regarding in view satellites and to compute pseudorange information;
7 storing the Doppler information;
8 detecting when the GPS information is experiencing blockage conditions and activating a
9 second mode of operation in response thereto, the second mode including, digitizing the GPS
10 signals at a predetermined rate to produce sampled GPS signals; and
11 receiving a signal having a Doppler shift error imposed by movement between a signal
12 source and the GPS receiver;
13 producing a plurality of complex first correlation values based upon the signal and a

14 code;
15 generating a plurality of complex second correlation values respectively from the first
16 correlation values, wherein generating includes combining a stored, associated, phase shift value
17 with each of the first correlation values to produce the second correlation values~~the second~~
18 ~~correlation values being phase-shifted by respective different amounts from corresponding first~~
19 ~~correlation values, so that the second correlation values exhibit less of the Doppler shift error~~
20 ~~than the first correlation values; and~~
21 combining the second correlation values to derive a complex third correlation value that
22 indicates a degree of correspondence of the code with the signal.

1 55. (currently amended) In a method for determining the position of a remote unit, a
2 process comprising:
3 receiving, at the remote unit from a transmission cell in a cellular communication system,
4 a Doppler information of a satellite in view of the remote unit;
5 computing, in a remote unit, position information for the satellite by using the Doppler
6 information without receiving and without using satellite ephemeris information;
7 when computing the position information, performing the following steps:
8 producing a plurality of complex first correlation values based upon the signal and a
9 code;
10 generating a plurality of complex second correlation values respectively from the first
11 correlation values, wherein generating includes combining a stored, associated, phase
12 shift value with each of the first correlation values to produce the second correlation
13 values~~the second correlation values being phase-shifted by respective different amounts~~
14 ~~from corresponding first correlation values, so that the second correlation values exhibit~~
15 ~~less of the Doppler shift error than the first correlation values; and~~
16 combining the second correlation values to derive a complex third correlation value
17 that indicates a degree of correspondence of the code with the signal.

1 56. (currently amended) A method of using a base station for providing a
2 communications link to a mobile GPS unit, the method comprising:
3 determining Doppler information of a satellite in view of the mobile GPS unit, wherein

4 the Doppler information is used by the mobile GPS unit to determine a position information for
5 the satellite;

6 transmitting from a transmission cell in a cellular communication system the Doppler
7 information of the satellite in view to the mobile GPS unit wherein the mobile GPS unit
8 determines the position information without receiving and without using satellite ephemeris
9 information;

10 when performing the determining step, performing the following steps:

11 receiving a signal having a Doppler shift error imposed by movement between a
12 satellite and a GPS receiver producing a plurality of complex first correlation values
13 based upon the signal and a code;

14 generating a plurality of complex second correlation values respectively from the first
15 correlation values, wherein generating includes combining a stored, associated, phase
16 shift value with each of the first correlation values to produce the second correlation
17 values~~the second correlation values being phase shifted by respective different amounts~~
18 ~~from corresponding first correlation values, so that the second correlation values exhibit~~
19 ~~less of the Doppler shift error than the first correlation values; and~~

20 combining the second correlation values to derive a complex third correlation value
21 that indicates a degree of correspondence of the code with the signal.

1 57. (currently amended) A method of determining the location of a remote object
2 comprising the steps of:

3 transporting a positioning sensor to a remote object;

4 repositioning the positioning sensor to a fix position such that the positioning sensor is
5 capable of receiving positioning signals, the fix position being in a known position relative to the
6 position of the remote sensor;

7 storing a predetermined amount of data in the positioning sensor while the positioning
8 sensor is located at the fix position, the data comprising the positioning signals;

9 processing the data to determine the location of the fix position;

10 computing the location of the remote object using the location of the fix position; and

11 when performing the processing steps, performing the following steps:

12 producing a plurality of complex first correlation values based upon the signal and a
13 code;

14 generating a plurality of complex second correlation values respectively from the first
15 correlation values, wherein generating includes combining a stored, associated, phase
16 shift value with each of the first correlation values to produce the second correlation
17 values~~the second correlation values being phase shifted by respective different amounts~~
18 ~~from corresponding first correlation values, so that the second correlation values exhibit~~
19 ~~less of the Doppler shift error than the first correlation values; and~~

20 combining the second correlation values to derive a complex third correlation value
21 that indicates a degree of correspondence of the code with the signal.

1 58. (currently amended) A method of tracking a remote object comprising the steps of:
2 fitting a remote object with a positioning sensor configured to receive and store
3 positioning information when the remote object is in a fix position;
4 positioning the remote object in a fix position such that the positioning sensor is capable
5 of detecting an activation signal;
6 processing and storing a predetermined amount of data in the positioning sensor, the data
7 comprising position information;
8 processing the data to determine the location of the fix position;
9 when processing the data, performing the following steps:
10 producing a plurality of complex first correlation values based upon the signal and a
11 code;

12 generating a plurality of complex second correlation values respectively from the first
13 correlation values, wherein generating includes combining a stored, associated, phase shift value
14 with each of the first correlation values to produce the second correlation values~~the second~~
15 ~~correlation values being phase shifted by respective different amounts from corresponding first~~
16 ~~correlation values, so that the second correlation values exhibit less of the Doppler shift error~~
17 ~~than the first correlation values; and~~
18 combining the second correlation values to derive a complex third correlation value
19 that indicates a degree of correspondence of the code with the signal.

1 59. (currently amended) A computer readable medium containing a computer program
2 having executable code for a GPS receiver, the computer program comprising:
3 first instructions for receiving GPS signals from in view satellites, the GPS signals
4 comprising pseudorandom (PN) codes;
5 second instructions for digitizing the GPS signals at a predetermined rate to produce
6 sampled GPS signals;
7 third instructions for storing the sampled GPS signals in a memory; and
8 fourth instructions for processing the sampled GPS signal by performing a plurality of
9 convolutions on the sampled GPS signals, the processing comprising performing the plurality of
10 convolutions on a corresponding plurality of blocks of the sampled GPS signals to provide a
11 plurality of corresponding results of each convolution and summing a plurality of mathematical
12 representations of the plurality of corresponding results to obtain a first position information; and
13 wherein the fourth in instructions are designed to:
14 produce a plurality of complex first correlation values based upon the signal and a
15 code;
16 generate a plurality of complex second correlation values respectively from the first
17 correlation values, wherein generating includes combining a stored, associated, phase
18 shift value with each of the first correlation values to produce the second correlation
19 values~~the second correlation values being phase shifted by respective different amounts~~
20 ~~from corresponding first correlation values, so that the second correlation values exhibit~~
21 ~~less of the Doppler shift error than the first correlation values; and~~
22 combine the second correlation values to derive a complex third correlation value that
23 indicates a degree of correspondence of the code with the signal.

1 60. (currently amended) A computer readable medium containing an executable
2 computer program for use in a digital processing system, the executable computer program when
3 executed in the digital processing system causing the digital processing system to perform the
4 steps of:
5 performing a plurality of convolutions of a corresponding plurality of blocks of sampled
6 GPS signals to provide a plurality of corresponding results of each convolution;

7 summing a plurality of mathematical representations of the plurality of corresponding
8 results to obtain a first position information; and
9 when performing the plurality of convolutions step, performing at least the following
10 steps:

11 producing a plurality of complex first correlation values based upon the signal and a
12 code;

13 generating a plurality of complex second correlation values respectively from the first
14 correlation values, wherein generating includes combining a stored, associated, phase
15 shift value with each of the first correlation values to produce the second correlation
16 values~~the second correlation values being phase shifted by respective different amounts~~
17 ~~from corresponding first correlation values, so that the second correlation values exhibit~~
18 ~~less of the Doppler shift error than the first correlation values; and~~

19 combining the second correlation values to derive a complex third correlation value
20 that indicates a degree of correspondence of the code with the signal.

1 61. (currently amended) A method of calibrating a local oscillator in a mobile GPS
2 receiver, the method comprising:

3 receiving a precision carrier frequency signal from a source providing the precision
4 carrier frequency;
5 automatically locking to the precision carrier frequency signal and providing a reference
6 signal;

7 calibrating the local oscillator with the reference signal, the local oscillator being used to
8 acquire GPS signals;

9 receiving a signal having a Doppler shift error imposed by movement between a signal
10 source and the GPS receiver;

11 producing a plurality of complex first correlation values based upon the signal and a
12 code;

13 generating a plurality of complex second correlation values respectively from the first
14 correlation values, wherein generating includes combining a stored, associated, phase shift value
15 with each of the first correlation values to produce the second correlation values~~the second~~

16 ~~correlation values being phase shifted by respective different amounts from corresponding first~~
17 ~~correlation values, so that the second correlation values exhibit less of the Doppler shift error~~
18 ~~than the first correlation values; and~~

19 combining the second correlation values to derive a complex third correlation value that
20 indicates a degree of correspondence of the code with the signal.

1 62. (currently amended) A method of using a base station to calibrate a local oscillator in
2 a mobile GPS receiver, the method comprising:

3 producing a first reference signal having a precision frequency;

4 modulating the first reference signal with a data signal to provide a precision carrier
5 frequency signal;

6 transmitting the precision carrier frequency signal to the mobile GPS receiver, the
7 precision carrier frequency signal being used to calibrate a local oscillator in the mobile GPS
8 receiver, the local oscillator being used to acquire GPS signals;

9 receiving a spread spectrum signal having a Doppler shift error imposed by movement
10 between a signal source and the GPS receiver;

11 producing a plurality of complex first correlation values based upon the signal and a
12 code;

13 generating a plurality of complex second correlation values respectively from the first
14 correlation values, wherein generating includes combining a stored, associated, phase shift value
15 with each of the first correlation values to produce the second correlation values~~the second~~

16 ~~correlation values being phase shifted by respective different amounts from corresponding first~~
17 ~~correlation values, so that the second correlation values exhibit less of the Doppler shift error~~
18 ~~than the first correlation values; and~~

19 combining the second correlation values to derive a complex third correlation value that
20 indicates a degree of correspondence of the code with the signal.

1 63. (currently amended) A method of deriving a local oscillator signal in a mobile GPS
2 receiver, the method comprising:

3 receiving a precision carrier frequency signal from a source providing the precision
4 carrier frequency signal;

5 automatically locking to the precision carrier frequency signal and providing a reference
6 signal;
7 using the reference signal to provide a local oscillator signal to acquire GPS signals;
8 receiving a spread spectrum signal having a Doppler shift error imposed by movement
9 between a signal source and the GPS receiver;
10 producing a plurality of complex first correlation values based upon the signal and a
11 code;
12 generating a plurality of complex second correlation values respectively from the first
13 correlation values, wherein generating includes combining a stored, associated, phase shift value
14 with each of the first correlation values to produce the second correlation values~~the second~~
15 ~~correlation values being phase shifted by respective different amounts from corresponding first~~
16 ~~correlation values, so that the second correlation values exhibit less of the Doppler shift error~~
17 ~~than the first correlation values; and~~
18 combining the second correlation values to derive a complex third correlation value that
19 indicates a degree of correspondence of the code with the signal.

42
Cont.

1 64. (currently amended) A method of processing position information, the method
2 comprising:
3 receiving SPS signals from at least one SPS satellite;
4 transmitting cell based communication signals between a communication system coupled
5 to the SPS receiver and a first cell based transceiver which is remotely positioned relative to the
6 SPS receiver wherein the cell based communication signals are wireless;
7 determining a first time measurement which represents a time of travel of a message in
8 the cell based communication signals in a cell based communication system which comprises a
9 first cell based transceiver and the communications system;
10 determining a second time measurement which represents a time of travel of the SPS
11 signals;
12 determining a position of the SPS receiver from at least one of the first time measurement
13 and the second time measurement, wherein the cell based communication signals are capable of
14 communicating data messages in a two-way direction between the first cell based transceiver and

15 the communication system; and
16 performing the following steps during at least one of the determining steps:
17 producing a plurality of complex first correlation values based upon the signal and a
18 code;
19 generating a plurality of complex second correlation values respectively from the first
20 correlation values, wherein generating includes combining a stored, associated, phase
21 shift value with each of the first correlation values to produce the second correlation
22 values~~the second correlation values being phase shifted by respective different amounts~~
23 ~~from corresponding first correlation values, so that the second correlation values exhibit~~
24 ~~less of the Doppler shift error than the first correlation values; and~~
25 combining the second correlation values to derive a complex third correlation value
26 that indicates a degree of correspondence of the code with the signal.

A2
Cont

1 65. (currently amended) A method of processing position information in a digital
2 processing system, the method comprising:
3 determining a first time measurement which represents a time of travel of a message in
4 cell based communication signals in a cell based communication system which comprises a first
5 cell based transceiver which communicates with the digital processing system and a
6 communication system which communicates in a wireless manner with the first cell based
7 transceiver;
8 determining a position of a SPS receiver from at least the first time measurement and a
9 second time measurement which represents a time of travel of SPS signals received at the SPS
10 receiver which is integrated with the communication system and is remotely located relative to
11 the first cell based transceiver and the digital processing system, wherein the cell based
12 communication signals are capable of communicating messages from the communication system
13 to the first cell based transceiver; and
14 performing the following steps when determining the position:
15 receiving a signal having a Doppler shift error imposed by movement between a
16 signal source and the GPS receiver;
17 producing a plurality of complex first correlation values based upon an SPS signal

18 and a code;

19 generating a plurality of complex second correlation values respectively from the first
20 correlation values, wherein generating includes combining a stored, associated, phase
21 shift value with each of the first correlation values to produce the second correlation
22 values~~the second correlation values being phase shifted by respective different amounts~~
23 ~~from corresponding first correlation values, so that the second correlation values exhibit~~
24 ~~less of the Doppler shift error than the first correlation values; and~~
25 combining the second correlation values to derive a complex third correlation value
26 that indicates a degree of correspondence of the code with the signal.

1 66. (currently amended) A method of controlling a communication link and processing
2 data representative of GPS signals from at least one satellite in a GPS receiver, the method
3 comprising:

4 processing the data representative of GPS signals from at least one satellite in a
5 processing unit, including performing a correlation function to determine a pseudorange based on
6 the data representative of GPS signals;

7 controlling communication signals through the communication link by using the
8 processing unit to perform the controlling and wherein the processing unit performs
9 demodulation of communication signals sent to the GPS receiver; and

10 when performing the processing step, performing at least the following steps:

11 receiving a signal having a Doppler shift error imposed by movement between a
12 signal source and the GPS receiver;

13 producing a plurality of complex first correlation values based upon the signal and a
14 code;

15 generating a plurality of complex second correlation values respectively from the first
16 correlation values, wherein generating includes combining a stored, associated, phase
17 shift value with each of the first correlation values to produce the second correlation
18 values~~the second correlation values being phase shifted by respective different amounts~~
19 ~~from corresponding first correlation values, so that the second correlation values exhibit~~
20 ~~less of the Doppler shift error than the first correlation values; and~~

pg
concl
22

combining the second correlation values to derive a complex third correlation value that indicates a degree of correspondence of the code with the signal.
